






版次 (Version)	変更内容 (Rev. Content)	変更者 (Change Person)



技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/15A	250V/12A
压线范围 (Wire Range)	28~14AWG	1.5mm²
工频耐压 (Frequency Voltage)	AC 2000V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	5~6mm	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PBT (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀镍 (Copper alloy, Ni plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	
方盒 (Cage)	铜合金, 镀镍 (Copper alloy, Ni plated)	

产品命名编码:
(Product Number Code):

GS005-5.0-XXP-1Y-00A (H)

产品型号 (Series No.):

—客户需求
(Customer Request)

极数 (No. of poles)

—塑体颜色(Housing Color)

1:单倍间距
(Single Pitch)
2:双倍间距
(Double Pitch)

1: 绿色 (Green)	7: 透明色 (Transparent)
2: 蓝色 (Blue)	8: 白色 (White)
3: 黑色 (Black)	9: 黄色 (Yellow)
4: 灰色 (Grey)	Y: 多种颜色 (Mixed Color)
5: 橙色 (Orange)	
6: 红色 (Red)	

产品为02P/03P拼接，L为拼接产品总长，P为PIN距，N为位数(有效位数为02P~XXP)，P=5.0												
N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	65.00
B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	. . .
L	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	120.00	
B	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	

Ant Electronic CO.,LTD				公差范围(Tolerance Range)	
				150~ ±1.50	
				60~150 ±1.00	
				30~60 ±0.60	
				6~30 ±0.40	
型号(Type): GS005-5. 0-XXP-1Y-00A (H)				0~6 ±0.25	
核准(Approval):		图号(Drawing NO.):		角度 (Angle)	X ±2°
审核(Audit):		单位(Units):mm 页码(Page): 1/1			XX ±1°
设计(Design):		比例(Scale):FULL		 版次(Version): TO	