





版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)



P=5.08mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~24P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	20.16	25.24	30.32	35.40	40.48	45.56	50.64	55.72	60.80	65.88	70.96	76.04
B	5.08	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96
F	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96	66.04	71.12
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	
L	81.12	86.20	91.28	96.36	101.44	106.52	111.60	116.68	121.76	126.84	131.92	
B	66.04	71.12	76.20	81.28	86.36	91.44	96.52	101.60	106.68	111.76	116.84	
F	76.20	81.28	86.36	91.44	96.52	101.60	106.68	111.76	116.84	121.92	127.00	



技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/16A	320V/20A
压线范围 (Wire Range)	/	/
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘电阻 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	/	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
/	/	

产品命名编码:

(Product Number Code):

产品型号 (Series No.)


极数 (No. of poles)

—客户需求

塑体颜色(Housing Color)

1:单倍间距 (Single Pitch)
2:双倍间距 (Double Pitch)

1: 绿色 (Green)	7: 透明色 (Transparent)
2: 蓝色 (Blue)	8: 白色 (White)
3: 黑色 (Black)	9: 黄色 (Yellow)
4: 灰色 (Grey)	Y: 多种颜色 (Mixed Color)
5: 橙色 (Orange)	
6: 红色 (Red)	

Ant Electronic CO.,LTD				公差范围(Tolerance Range)		
				150~	±1.50	
型号(Type): GSP001JBW-5. 08-XXP-1Y-00A (H)				60~150		±1.00
				30~60		±0.60
核准(Approval):				6~30		±0.40
				0~6		±0.25
图号(Drawing NO.):		角度(Angle)		X	±2°	
				XX	±1°	
审核(Audit):		单位(Units):mm	页码(Page): 1/1			
设计(Design):		比例(Scale):FULL			版次(Version): TO	