

A

B

C

D

E

A

B

C

D

E

版次 (Vension)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/16A	320V/20A
压线范围 (Wire Range)	/	/
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	/	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
/	/	

产品命名编码:

(Product Number Code):

GSP001RC-5. 0-XXP-1Y-00A (H)

产品型号 (Series No.)

客户需求

(Customer Request)





极数 (No. of poles)

塑体颜色 (Housing Color)

1: 单倍间距
(Single Pitch)
2: 双倍间距
(Double Pitch)

1: 绿色 (Green) 7: 透明色
2: 蓝色 (Blue) (Transparent)
3: 黑色 (Black) 8: 白色 (White)
4: 灰色 (Grey) 9: 黄色 (Yellow)
5: 橙色 (Orange) Y: 多种颜色
6: 红色 (Red) (Mixed Color)

Ant Electronic CO.,LTD			公差范围 (Tolerance Range)	
			150~	±1.50
			60~150	±1.00
型号 (Type): GSP001RC-5. 0-XXP-1Y-00A (H)			30~60	±0.60
核准 (Approval):			6~30	±0.40
审核 (Audit):			0~6	±0.25
设计 (Design):			角度 (Angle)	X ±2° XX ±1°
比例 (Scale): FULL			版次 (Version): T0	



L为总体总长, P为PIN距, N为位数 (有效位数为02P~24P), P=5.00												
N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	11.60	16.60	21.60	26.60	31.60	36.60	41.60	46.60	51.60	56.60	61.60	66.60
B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	
L	71.60	76.60	81.60	86.60	91.60	96.60	101.60	106.60	111.60	116.60	121.60	
B	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	