



版次 (Version)	変更内容 (Rev. Content)	変更者 (Change Person)



技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	150V/10A	130V/10A
压线范围 (Wire Range)	26~16AWG	0.5~1.0mm²
工频耐压 (Frequency Voltage)	AC 2000V	
冲击耐压 (Rated Surge Voltage)	2500V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	5mm	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	
方盒 (Cage)	铜合金, 镀镍 (Copper alloy, Ni plated)	



产品命名编码:

(Product Number Code):

GS034H-3. 81-XXP-1Y-00A (H)

产品型号 (Series No.)-

客户需求

(Customer Request)

极数 (No. of poles)

—塑体颜色(Housing Color)

1:单倍间距
(Single Pitch)
2:双倍间距
(Double Pitch)

1: 绿色 (Green)	7: 透明色 (Transparent)
2: 蓝色 (Blue)	8: 白色 (White)
3: 黑色 (Black)	9: 黄色 (Yellow)
4: 灰色 (Grey)	Y: 多种颜色 (Mixed Color)
5: 橙色 (Orange)	
6: 红色 (Red)	

P=3.81mm, N为孔位数(N for hole digits), 有效位数为(Significant Digits): 02P~XXP												
N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29	38.10	41.91	45.72	49.53
B	3.81	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29	38.10	41.91	45.72
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	...
L	53.34	57.15	60.96	64.77	68.58	72.39	76.20	80.01	83.82	87.63	91.44	
B	49.53	53.34	57.15	60.96	64.77	68.58	72.39	76.20	80.01	83.82	87.63	

Ant Electronic CO.,LTD				公差范围(Tolerance Range)	
				150~	±1.50
型号(Type): GS034H-3. 81-XXP-1Y-00A (H)				60~150	±1.00
				30~60	±0.60
核准(Approval):				6~30	±0.40
				0~6	±0.25
图号(Drawing NO.):		角度(Angle)		X	±2°
				X,X	±1°
审核(Audit):		单位(Units):mm	页码(Page): 1/1		
设计(Design):		比例(Scale):FULL			版次 (Version): TO