

A





B

C

D

E

12345678



版次 (Vension)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/12A	320V/20A
压线范围 (Wire Range)	26~12WG	2.5mm²
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	10mm	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
弹片 (Spring)	不锈钢 (Stainless)	

产品命名编码:

(Product Number Code):

GSP001DF-5. 08-XXP-1Y-00A (H)

产品型号 (Series No.)

客户需求

(Customer Request)

极数 (No. of poles)

塑体颜色 (Housing Color)

1:单倍间距
(Single Pitch)
2:双倍间距
(Double Pitch)

1:绿色 (Green) 7:透明色
(Transparent)
2:蓝色 (Blue)
3:黑色 (Black) 8:白色 (White)
4:灰色 (Grey) 9:黄色 (Yellow)
5:橙色 (Orange) Y:多种颜色
6:红色 (Red) (Mixed Color)

P=5.08mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~24P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	11.06	16.14	21.22	26.30	31.38	36.46	41.54	46.62	51.70	56.78	61.86	66.94
B	5.08	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	
L	72.02	77.10	82.18	87.26	92.34	97.42	102.50	107.58	112.66	117.74	122.82	
B	66.04	71.12	76.20	81.28	86.36	91.44	96.52	101.60	106.68	111.76	116.84	

Ant Electronic CO.,LTD

型号 (Type): GSP001DF-5. 08-XXP-1Y-00A (H)

核准 (Approval):

图号 (Drawing NO.):


审核 (Audit):

单位 (Units): mm

页码 (Page): 1/1

设计 (Design):

比例 (Scale): FULL



版次 (Version): T0

公差范围 (Tolerance Range)	
150~	±1.50
60~150	±1.00
30~60	±0.60
6~30	±0.40
0~6	±0.25
角度 (Angle)	X ±2° XX ±1°